

OLFLEX® TC 600/ 600 S

For Exposed Run, no conduit is needed.



OLFLEX® TC 600: Flexible Tray Cable

Part Number	Number of Conductors includes ground	Nominal Outer Diameter inches	mm	Copper Weight lbs/mft	Approx. Weight lbs/mft	kg/km	Part Number	Number of Conductors includes ground	Nominal Outer Diameter inches	mm	Copper Weight lbs/mft	Approx. Weight lbs/mft	kg/km
18 AWG (7 strand) 1.00 mm ²							12 AWG (19 strand) 3.30 mm ²						
211802	2	.273	6.9	13	42	63	211407	7	.439	11.2	94	164	244
211803	3	.287	7.3	16	55	82	211409	9	.510	13.0	121	218	324
211804	4	.310	7.9	21	64	95	211410	10	.585	14.9	135	242	360
211805	5	.335	8.5	27	75	112	211412	12	.602	15.3	162	298	443
211807	7	.361	9.2	37	97	144	211416	16	.665	16.9	215	373	555
211809	9	.416	10.6	48	109	162	211419	19	.699	17.8	256	450	670
211810	10	.449	11.4	53	115	171	211425	25	.807	20.5	337	569	847
211812	12	.462	11.7	64	166	247	10 AWG (19 strand) 5.32 mm ²						
211815	15	.511	13.0	80	207	308	211202	2	.363	9.2	50	85	127
211819	19	.569	14.5	101	263	391	211203**	3	.384	9.8	64	111	165
211825	25	.648	16.6	133	312	464	211204**	4	.419	10.6	86	148	220
16 AWG (7 strand) 1.32 mm ²							211205	5	.456	11.6	107	181	269
211602	2	.295	7.5	18	52	77	211206	6	.496	12.6	128	250	372
211603	3	.311	7.9	25	67	100	211207	7	.496	12.6	150	324	482
211604	4	.337	8.6	34	80	119	211209	9	.610	15.5	192	360	536
211605	5	.364	9.3	42	95	141	211212	12	.681	17.3	257	432	643
211606	6	.394	10.0	51	123	183	211216	16	.754	19.2	342	540	804
211607	7	.394	10.0	59	123	183	211219	19	.794	20.2	406	684	1018
211609	9	.455	11.6	76	166	247	211220	20	.835	21.2	428	720	1071
211610	10	.493	12.5	85	184	273	211225	25	.960	24.4	535	900	1339
211612	12	.508	12.9	101	213	317	8 AWG (19 strand) 13.2 mm ²						
211616	16	.594	15.1	135	246	366	211002	2	.439	11.2	74	148	220
211618	18	.624	15.9	161	286	426	211003**	3	.466	11.9	102	193	287
211619	19	.624	15.9	161	286	426	211004**	4	.511	13.0	136	257	382
211620	20	.655	16.6	169	301	448	211005	5	.591	15.0	170	307	457
211625	25	.718	18.2	211	312	464	211007	7	.642	16.3	238	430	640
14 AWG (19 strand) 2.08 mm ²							211009	9	.748	19.0	306	549	817
211402	2	.325	8.3	30	65	96	211012	12	.839	21.3	408	737	1097
211403**	3	.343	8.7	40	84	125	211019	19	1.024	26.0	646	1178	1753
211404**	4	.373	9.5	54	104	155	6 AWG (19 strand) 8.38 mm ²						
211405	5	.405	10.3	67	124	185	211804	4	.943	24.0	245	597	888
211406	6	.439	11.2	81	164	244	211604	4	1.101	28.0	393	838	1297

OLFLEX® TC 600 S: Shielded Flexible Tray Cable

SunArx Actuator Wire

Part Number	Number of Conductors includes ground	Nominal Outer Diameter inches	mm	Copper Weight lbs/mft	Approx. Weight lbs/mft	kg/km	Part Number	Number of Conductors includes ground	Nominal Outer Diameter inches	mm	Copper Weight lbs/mft	Approx. Weight lbs/mft	kg/km
18 AWG (7 strand) 1.00 mm ²							12 AWG (19 strand) 3.30 mm ²						
211802S	2	.276	7.0	13	44	65	211406S	6	.442	11.2	81	169	251
211803S	3	.290	7.3	16	57	84	211407S	7	.442	11.2	94	169	251
211804S	4	.313	7.9	21	66	98	211409S	9	.513	13.0	121	225	334
211805S	5	.338	8.5	27	77	115	211410S	10	.588	14.9	135	249	371
211807S	7	.364	9.2	37	100	148	211412S	12	.605	15.3	162	307	456
211809S	9	.419	10.6	48	112	167	211416S	16	.668	16.9	215	384	572
211810S	10	.452	11.4	53	118	176	211419S	19	.702	17.8	256	464	690
211812S	12	.465	11.7	64	171	254	211425S	25	.810	20.5	337	586	872
211815S	15	.514	13.0	80	213	317	10 AWG (19 strand) 5.32 mm ²						
211819S	19	.572	14.5	101	271	403	211202S	2	.366	9.3	50	89	132
211825S	25	.651	16.6	133	321	478	211203S**	3	.387	9.8	64	114	170
16 AWG (7 strand) 1.32 mm ²							211204S**	4	.422	10.6	86	152	227
211602S	2	.298	7.6	18	54	80	211205S	5	.459	11.6	107	186	277
211603S	3	.314	7.9	25	69	103	211206S	6	.499	12.6	128	258	383
211604S	4	.340	8.6	34	82	123	211207S	7	.499	12.6	150	334	496
211605S	5	.367	9.3	42	98	145	211209S	9	.613	15.5	192	371	552
211606S	6	.397	10.0	51	127	188	211212S	12	.684	17.3	257	445	662
211607S	7	.397	10.0	59	127	188	211216S	16	.757	19.2	342	556	828
211609S	9	.458	11.6	76	171	254	211219S	19	.797	20.2	406	705	1049
211610S	10	.496	12.6	85	190	281	211220S	20	.883	21.4	428	742	1103
211612S	12	.511	12.9	101	219	327	211225S	25	.963	24.4	535	927	1379
211616S	16	.597	15.1	135	253	377	10 AWG (19 strand) 5.32 mm ²						
211619S	19	.627	15.9	161	295	439	211002S	2	.422	11.2	74	154	229
211620S	20	.658	16.6	169	310	461	211003S**	3	.469	11.9	102	199	296
211625S	25	.721	18.2	211	321	478	211004S**	4	.514	13.0	136	265	393
14 AWG (19 strand) 2.08 mm ²							211005S	5	.594	15.0	170	316	471
211402S	2	.328	8.3	30	67	100	211007S	7	.645	16.3	238	443	659
211403S**	3	.346	8.7	40	87	129	211009S	9	.751	19.0	306	565	842
211404S**	4	.376	9.5	54	107	160	211012S	12	.842	21.3	408	759	1130
211405S	5	.408	10.3	67	128	191	211019S	19	1.027	26.0	646	1213	1806