



by Schneider Electric

List Price \$488.00 USD

Availability **Stock Item:** This item is normally stocked in our distribution facility.

Technical Characteristics

| | |
|------------------------------|--|
| Disconnect Type | Non-Fusible |
| Enclosure Rating | NEMA 3R |
| Maximum Voltage Rating | 600V |
| Short Circuit Current Rating | 200kA(max) |
| Wire Size | #12 to #2 AWG(Al) or #14 to #2 AWG(Cu) |
| Action | Single Throw |
| Enclosure Type | Rainproof and Sleet/Ice proof (Indoor/Outdoor) |
| Mounting Type | Surface |
| Depth | 4.88 Inches |
| Ampere Rating | 30A |
| Enclosure Material | Galvannealed Steel |
| Number of Poles | 3-Pole |
| Height | 14.88 Inches |
| Approvals | UL Listed |
| Terminal Type | Lugs |
| Width | 6.63 Inches |
| Factory Installed Neutral | No |
| Electrical Interlock | None |
| Type of Duty | Heavy Duty |

Shipping and Ordering

| | |
|-------------------|--|
| Category | 00009 - Safety Switch, Heavy Duty, 2 & 3 Pole, 30-200 Amp, Outdoor |
| Discount Schedule | DE1 |
| Article Number | 785901505600 |
| Package Quantity | 1 |
| Weight | 8.16 lbs. |
| Availability Code | S |
| Returnability | Y |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Available From:



www.SolarPanelStore.com

Generated: 08/16/2010 12:56:42