



by Schneider Electric

List Price \$876.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.**

Technical Characteristics

| | |
|------------------------------|------------------------------------------------|
| Type of Duty | Heavy Duty |
| Electrical Interlock | None |
| Depth | 6.38 Inches |
| Disconnect Type | Non-Fusible |
| Maximum Voltage Rating | 600V |
| Width | 9.00 Inches |
| Enclosure Rating | NEMA 3R |
| Height | 17.50 Inches |
| Short Circuit Current Rating | 200kA(max) |
| Enclosure Type | Rainproof and Sleet/Ice proof (Indoor/Outdoor) |
| Action | Single Throw |
| Mounting Type | Surface |
| Ampere Rating | 60A |
| Enclosure Material | Galvannealed Steel |
| Number of Poles | 3-Pole |
| Approvals | UL Listed |
| Terminal Type | Lugs |
| Factory Installed Neutral | No |
| Wire Size | #12 to #2 AWG(Al) or #14 to #2 AWG(Cu) |

Shipping and Ordering

| | |
|-------------------|-------------------------------------------------------------------------|
| Category | 00009 - Safety Switch, Heavy Duty, 2 & 3 Pole, 30-200 Amp, Outdoor |
| Discount Schedule | DE1 |
| GTIN | 00785901505617 |
| Package Quantity | 1 |
| Weight | 15.23 lbs. |
| Availability Code | Stock Item: This item is normally stocked in our distribution facility. |
| Returnability | Y |
| Country of Origin | US |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.